

Bay State Wire & Cable

Data Communications Cable Specification

Bay State Wire & Cable Part #: PC4C18SS

DESCRIPTION: 18/4 STRANDED SHIELDED CL3P/CMP/FPLP FT6 PLENUM CABLE

CONSTRUCTION: This cable consists of four bare copper insulated conductors, cabled with an overall shield and drain wire, and an overall jacket.

APPROVALS: UL Standard 13 and 444, NEC Articles 725 and 800.

APPLICATION: Class 3 Power Limited Circuit Cable and Communications Cable Used in Plenum Applications

1. Conductor
 - 1.1 AWG a Stranding: 18 AWG, Class B 7 Strands
 - 1.2 Material: Annealed Bare Copper
2. Insulation
 - 2.1 Material: Plenum Rated Polyvinylchloride (SGPVC)
 - 2.2 Wall Thickness: 0.008"
3. Color Code
 - 3.1 Code: Black, Red, White, Green
4. Assembly
 - 4.1 Cable Lay Length: 3.00" Nominal
 - 4.2 Cable Shield: Aluminum/Mylar Tape -100% coverage
 - 4.3 Cable Drain Wire: 24 AWG, 7 Strand Tinned Copper
 - 4.4 Cable Binder: N/A
5. Jacket
 - 5.1 Material: Plenum Rated Polyvinylchloride (SGPVC)
 - 5.2 Wall Thickness: 0.015"
 - 5.3 Diameter: 0.185"
 - 5.4 Color: White
 - 5.5 Weight: 29.9 lbs/Mft.
6. Markings
 - 6.1 Type: Cable shall be permanently identified via surface inkjet print
 - 6.2 Legend: 18AWG 2C SHLD (UL) CL3P OR CMP C(UL)US 75°C FT-6
"ROMS"
7. Standards
 - 7.1 UL listed as Type CL3P or CMP c(UL)us 75 °C, FT-6
 - 7.2 All materials used in the manufacture of this cable are RoHS compliant

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION